

# L-42DT

## METAPACE

Highly flexible all-rounder  
for the desktop

### Technical Specifications

Print method	Direct thermal, thermal transfer
Print speed	max. 178 mm/sec.
Print length	6–2000 mm
Print width	max. 108 mm
Resolution	203 dpi, 300 dpi (optional)
Sensor	Transmissive, Reflective Ribbon End, Head Open

Media type	Gap, Black Mark, Notch, Continuous, Fan-Fold
Width	20–110 mm
Roll diameter	max. 130 mm
Core diameter	25.4–38.1 mm
Media thickness	0.06–0.20 mm

Ribbon type	Wax, Wax / Resin, Resin (Outside)
Ribbon width	110 mm
Ribbon length	max. 74 m
Core inner diameter	12.7 mm

Memory	64 MB SDRAM, 128 MB FlashROM
Interfaces	USB 2.0, serial/parallel, Wi-Fi/Ethernet (opt.)
Power	AC 100–240V, 50/60 Hz, DC 24 V, 2,5 A
Barcodes	All standard 1D and 2D barcodes
Reliability	MTBF: 25 km TPH, Auto-Cutter: 0.3 million cuts

Emulation	EPL (compatible), EPL II (compatible), ZPL (compatible), ZPL II (compatible), SLCS
SDK	Android SDK, Windows SDK
Drivers	Windows 7, 8, 10, Linux, Mac OS X
Label designer	Metapace Label Designer Software

Standard	USB cable, power supply, power cord, driver CD, design software
Optional	Auto-Cutter, Dispenser, Ethernet

Period	24 months
--------	-----------

Dimensions (WxHxD)	200 × 252 × 173 mm
Weight	2.35 kg
Colour	Black

Temperature	Operating: 5 °C to 40 °C (41 °F to 104 °F) Storage: -20 °C to 60 °C (-4 °F to 140 °F)
Humidity	Operating: 10 % to 80 % RH Storage: 10 % to 90 % RH

### Highlights

- + Affordable direct thermal/thermal transfer desktop label printer
- + Extremely fast printing, with up to 178 mm/sec.
- + Compact housing, large Flash and RAM memory
- + Versatile connectivity: USB, RS232, parallel, optional Ethernet and Wi-Fi
- + Complete package with accessories, just unpack and start



**Drivers**  
by Seagull™

