

S-62

METAPACE S-62 COMPETITIVELY PRICED IMAGER

TECHNICAL SPECIFICATIONS

PROPERTIES

Type	2D imager
Light source	Lighting: white LED; aiming: red LED, 617 nm
Movement tolerance	100 mm/s, 13 mils UPC
Print contrast	Min. 35 % reflectance difference
Scanning angle	Rotation: $\pm 180^\circ$; pitch: $\pm 65^\circ$; skew: $\pm 60^\circ$
Supported barcodes	UPC/EAN, UPC/EAN with supplementals, UCC/EAN 128, Code 39, Code 39 Full ASCII, Code 39 TriOptic, Code 128, Code 128 Full ASCII, Codabar, Interleaved 2 of 5, Discrete 2 of 5, Code 93, MSI, Code 11, IATA, GS1 DataBar (formerly RSS) variants, Chinese 2 of 5 and Codablock, Code 49, PDF417, QR-Code, DataMatrix, MaxiCode, Aztec-Code

ELECTRONICS

Laser safety	EN class B; IEC62471
Voltage	5 V \pm 5% @ 400 mA

INTERFACE

I/F ports	USB
-----------	-----

SPECIFICS

Impact resistance	Resists multiple 1 m drops to concrete
Protection rating	IP40

ENVIRONMENT

Operating temperature	0°C – 40°C
Storage temperature	-40°C – 60°C
Humidity	5% – 95% RH (non-condensing)

HOUSING

Dimensions (W x H x D)	95 x 68 x 152 mm
Weight	125 g (without cable)
Colour	Black

WARRANTY

Period	60 months
--------	-----------

HIGHLIGHTS

- + Multi-faceted 2D area imager at a great price
- + Captures all common 1D, 2D, postal and stacked codes
- + Versatile: handheld and presentation modes
- + Scan confirmation via green LED and beeper

