

MS7180 OrbitCG

Omnidirectional Laser Scanner

Honeywell's MS7180 OrbitCG® provides a stylish solution for omnidirectional and menu-scanning applications where counter space is at a premium.

OrbitCG combines the power of patented CodeGate® technology with many of the outstanding features already found in the MS7120 Orbit®—the all-time, best-selling small omnidirectional hands-free scanner.

CodeGate technology allows the user to easily target the desired bar code and complete data transmission with the push of a single button, making OrbitCG ideal for targeted or menu scanning applications.

This innovative, elegant and affordable solution to convenience retail applications also safeguards long-term infrastructure commitments.

In the event of a change in POS system or software, OrbitCG easily updates firmware via its patented MetroSet®2 configuration software—provided free by Honeywell. Use either a USB or RS232 interface to perform configuration updates.

Based on the original MS7120 Orbit's award-winning design, OrbitCG's shape enables hand-held scanning of large, bulky items. For added flexibility, the scanning head can be tilted within a 30° range to accommodate objects of various sizes and shapes.

Standard features include an EAS antenna integration for tag deactivation, power save mode, data editing, OPOS/JPOS compatibility for easy installation and user-replaceable cables.

For more information on the MS7180 OrbitCG omnidirectional laser scanner, please visit www.honeywell.com/aidc



Features

- **20 Scan Line Omnidirectional Pattern:** Provides aggressive scanning as an additional benefit to hand presentation applications
- **Single-Line Option:** With the push of a button, switch to a targeted scan ideal for menu scanning
- **Adjustable Scan Head:** Ability to tilt scanner 30° for targeted scanning or larger products
- **Flash ROM:** Protects POS investment with free firmware updates via MetroSet®2 software and standard PC
- **Built In RF EAS Antenna:** Increases efficiency by simultaneously deactivating RF EAS tags and decoding bar codes

MS7180 OrbitCG Technical Specifications

Operational

Light Source	Visible Laser Diode 650 nm $\pm$ 10 nm
Visual Indicators	Blue = ready to scan; White = good read
Host System Interfaces	USB, RS232, Keyboard Wedge, IBM 46xx (RS485), Light Pen Wand Emulation

Mechanical

Dimensions (LxWxH)	105 mm x 102 mm x 150 mm (4.1" x 4.0" x 5.9")
Weight	400 g (14.1 oz)

Electrical

Input Voltage	5 VDC $\pm$ 0.25 V
Operating Power (typical)	900 mW (180 mA @ 5 V)
Standby Power (typical)	850 mW (170 mA @ 5 V)
DC Transformers	Class 2: 5.2 VDC @ 1 A
Laser Class	Class 1: IEC60825-1, EN60825-1
EMC	FCC Part 15, ICES-003, EN55022 Class B

Environmental

Operating Temperature	0°C to 40°C (32°F to 104°F)
Storage Temperature	-40°C to 60°C (-40°F to 140°F)
Humidity	5% to 95% relative humidity, non-condensing
Drop	Designed to withstand 1.2 m (4') drops
Environmental Sealing	Sealed to resist airborne particulate contaminants
Light Levels	4842 Lux (450 foot-candles)

Scan Performance

Scan Pattern	Omnidirectional: 5 fields of 4 parallel lines; Button activated single line
Scan Speed	Omnidirectional: 1120 scan lines per second; Single-line: 56 scan lines per second
Print Contrast	35% minimum reflectance difference
Pitch, Skew	60°, 60°
Decode Capability	Reads standard 1D and GS1 DataBar symbologies. Visit www.honeywell.com/aidc/symbologies for details.
Warranty	3 year factory warranty



For more information:

www.honeywell.com/aidc

Honeywell Security & Data Collection

Honeywell Scanning & Mobility
90 Coles Road
Blackwood, NJ 08012
856.228.8100
www.honeywell.com

Typical Performance*	
Narrow Width	Depth of Field
5.2 mil	0 mm - 50 mm (0" - 2.0")
7.5 mil	0 mm - 150 mm (0" - 5.9")
10 mil	0 mm - 220 mm (0" - 8.7")
13 mil	0 mm - 275 mm (0" - 10.8")
26 mil	0 mm - 300 mm (0" - 11.8")
*Resolution: 5 mil (0.125 mm)	
*Performance may be impacted by bar code quality and environmental conditions	

Honeywell