



SIMPLE TO INTEGRATE

Designed for easy integration, the Gryphon I GFS4100 reader provides a simple 'plug-and-play' solution for system designers. Constructed using high-impact resin to withstand repeated cleanings with solvents and disinfectant solutions, the sealed enclosure meets industrial standards against water and particulates to provide dependable and reliable scanning performance.

ADVANCED IMAGING TECHNOLOGY

The Gryphon I GFS4100 OEM module shares the same excellent reading characteristics found in the premium line of Gryphon™ 4100 series of handheld devices. Featuring outstanding near-field reading, a wide angle field-of-view, improved motion tolerance and snappy reading, it also offers integrators excellent performance on decoding poor or damaged codes. As with all Gryphon readers, the GFS4100 reader offers users additional good-read visual confirmation with Datalogic's patented 'Green Spot' technology.

CONTINUOUS SCANNING CAPABILITY

The Gryphon I GFS4100 reader supports several modes that can be used as a trigger. The module has the ability to automatically sense objects and trigger itself. A continuous scan mode transmits data whenever a bar code passes into its field of view. The reader can be triggered remotely using input from programmable logic controller (PLC) or sensor.



FEATURES

- High-speed imaging for fast moving codes
- Read rate: 320 reads/second
- Excellent near-field reading at the scan window
- Supports all common linear (1D) bar codes including GS1 DataBar™
- Reads high resolution bar codes up to 3 mils
- Datalogic's patented Green Spot for good-read feedback
- Integrated good-read beeper
- Automatic sensing or manual trigger options available
- Integrated interface cable
- High-impact resin creates a solvent-tolerant enclosure
- Water and Particulate Sealing Rating: IP54
- EASEOFCARE Service Plans offer a wide range of service options to protect your investment, ensuring maximum productivity and ROI

INDUSTRY-APPLICATIONS

- OEM Applications:
 - Service Kiosks
 - Price Verifiers
 - Ticket Readers
 - Document Handling
 - Medical Laboratories
 - Vending Machines
 - Additional Automated Equipment

DECODING CAPABILITY

1D / LINEAR CODES
Autodiscriminates all standard 1D codes including GS1 DataBar™ linear codes.

ELECTRICAL

CURRENT
Operating (Typical): 390 mA
Standby/Idle (Typical): GFS4170: < 2.5 mA

INPUT VOLTAGE
5 VDC +/- 5%

ENVIRONMENTAL

AMBIENT LIGHT
DROPP RESISTANCE
0 - 100,000 lux
Withstands repeated drops from 0.76 m / 2.50 ft onto a concrete surface

ESD PROTECTION (AIR DISCHARGE)
HUMIDITY (NON-CONDENSING)
PARTICULATE AND WATER SEALING
TEMPERATURE
16 kV
95%
IP54
Operating: 0 to 50 °C / 32 to 122 °F
Storage/Transport: -25 to 50 °C / -13 to 122 °F

INTERFACES

INTERFACES
RS-232; USB

PHYSICAL CHARACTERISTICS

COLORS AVAILABLE
Grey; Other colors and custom logo options are available for minimum quantity purchase.

DIMENSIONS
WEIGHT
3.9 x 5.7 x 5.8 cm / 1.5 x 2.2 x 2.3 in
170.0 g / 6.0 oz (including a 2.0 m / 6.6 ft RS-232 cable)

READING PERFORMANCE

IMAGER SENSOR
LIGHT SOURCE
PRINT CONTRAST RATIO (MINIMUM)
READ RATE (MAXIMUM)
READING ANGLE
READING INDICATORS
RESOLUTION (MAXIMUM)
CCD Solid State
Illumination: Dual LED Array 630 - 670 nm
15%
320 reads/sec.
Pitch: +/- 65°; Roll (Tilt): +/- 35°; Skew (Yaw): +/- 65°
Beeper; Datalogic 'Green Spot' Good Read Feedback; Good Read LED
0.076 mm / 3 mils

READING RANGES

TYPICAL DEPTH OF FIELD
Minimum distance determined by symbol length and scan angle.
Printing resolution, contrast, and ambient light dependent.
5 mils: 5.0 to 16.0 cm / 2.0 to 6.3 in
8 mils: 3.0 to 27.0 cm / 1.2 to 10.6 in
10 mils: 1.5 to 30.0 cm / 0.6 to 11.8 in
13 mils: 3.0 to 40.0 cm / 1.2 to 15.7 in
20 mils: up to 60.0 cm / up to 23.6 in

SAFETY & REGULATORY

AGENCY APPROVALS
The product meets necessary safety and regulatory approvals for its intended use.
The Quick Reference Guide for this product can be referred to for a complete list of certifications.
Complies to China RoHS; Complies to EU RoHS IEC 60825-1 Class 1 LED Product

ENVIRONMENTAL COMPLIANCE
LED CLASSIFICATION

UTILITIES

DATALOGIC ALADDIN™
Datalogic Aladdin configuration program is available for download at no charge.

OPOS / JAVAPOS
JavaPOS Utilities are available for download at no charge.
OPOS Utilities are available for download at no charge.

REMOTE HOST DOWNLOAD
Lowers service costs and improves operations.

WARRANTY

WARRANTY
3-Year Factory Warranty

