



# badgy 200

## A COMPLETE SOLUTION



■ Oli e card en f la e librar




■ E\_Ri\_Badge\_S\_dif card  
f er\_R ali a iR. f are +  
(i q di g in f f r f r t da aba g)

■ RibbR i a car ridge  
f r ea i g ha dli g



- LED cR. f r f a el
- 38 g cR. d e r cR f card
- 25-card feeder
- 25-card R. f. h f f er
- USB f r.



■ CR. f r f a ble a ck  
f r f 100 f r i  
(cR f ribbR. a d card)

### GENERAL FEATURES

- Single-sided printing
- Edge-Redge printing
- CR f. b l i n a i R. a d n i R f c h r f n t e h e r n a l r a f e r
- 300 dpi
- 2 million cards
- 16 MB RAM

### PRINTING PERFORMANCES

- CR f. (YMCKO): 38 cards (95 cards)
- MR. f c h r f n t e: 11 cards (325 cards)

### INTERFACES

- USB 2.0 (1.1 and 3.0 compatible)

### SAFETY

- Safety Key Lock

### DISPLAY

- LED
- Graphics: Ricca iR. f. clea i g a l e r f. e d f r. ribbR. a l e r, ribbR. c l e R e d, e c.

### CARD MANAGEMENT AND SPECIFICATIONS

- Feeder capacity: 25 cards (0.76 mm) 30 mm R40 card (0.50 mm) 20 mm
- QR code printer capacity: 25 cards (0.76 mm) 30 mm R40 card (0.50 mm) 20 mm
- Card thickness: 0.50 mm (R0.76 mm) (20 R30 mm), 0.76 mm (R40 mm)
- Card type: PVC card
- Card format: ISO CR-80 ISO 7810 (53.98 85.60 mm)

### BADGY RIBBONS

To maximize the quality and durability of the printed cards, the lifespan of the print head, and the overall printer reliability, use the recommended ribbons.

- Ribbon capacity:
  - YMCKO (included): 100 prints/roll
  - Black monochrome ribbon: 500 prints/roll
- Automatic decoder and card reader
- Ribbon in a car ridge feeder has a lid
- Integrated ribbon guide for MR. f c h r f n t e r i i g

### SOFTWARE

- Software included in E\_Ri\_Badge\_S\_dif f r f de i g i g a d f r i i g badge
  - Import data from a database
  - Operating systems:
    - Windows: XP SP3 32/64, Vista 32/64, W7 32/64, W8 32/64
    - Mac OS X 10.6, 10.7, 10.8, 10.9
- Software included in Badg\_P r e n t a t i o n f r f W i d o w s
  - Driver
  - Printer management and configuration tool with graphic Ricca iR. f.
  - 24/7 online support
  - Compatible with Windows: XP SP3 32/64, Vista 32/64, W7 32/64, W8 32/64
- Software included in the Mac OS X driver (for 10.6)

### ECO-FRIENDLY DESIGN, CERTIFICATIONS AND STATEMENT OF COMPLIANCE

- Pre-regulated and reduced electricity consumption
- EPEAT 2009/125/CE
- CE, FCC, VCCI, BIS, CCC, KC
- RoHS

### POWER

- Power supply: 100-240 V AC, 50-60 Hz, 1.8 A
- Power: 24 W DC, 2.7 A

### OPERATING ENVIRONMENT

- Minimum operating temperature: 15 / 30 C (59 / 86 F)
- Humidity: 20% RH (max) - CR de i g
- Minimum operating temperature: -5 / +70 C (23 / 158 F)
- Storage humidity: 20% RH (max) - CR de i g
- Operating humidity: 15 - 85% RH

### PACKAGING CONTENT

- Printer
- CR. f r f a ble
  - Color ribbon (YMCKO): 100 prints
  - 100 blank PVC cards (0.76 mm - 30 mm)
- Manual and CD-ROM for E\_Ri\_Badge\_S\_dif f r f are, a d card en f la e
- USB cable
- Power supply and cable

### SIZE AND WEIGHT

- CR f. l e e r a c k e d f r i r.
  - Dimensions (H x W x D): 315 x 385 x 285 mm (12.40" 15.15" 11.22")
  - Weight: 3.95 kg (8.71 lbs)
- Printer:
  - Dimensions (H x W x D): 147 x 200 x 276 mm (5.78" 7.87" 10.86")
  - Weight: 1.7 kg (3.75 lbs)

### WARRANTY

- 1-year warranty on the print head
- Warranty is available as an option

1 Defect Report Form

### EUROPE - MIDDLE-EAST - AFRICA

E\_Ri\_Card\_P r i e r - 14 a e. e de la FR. ai e - ZIA ger. Be a c R e  
49070 Bea c R e - Fra ce  
T +33 (0) 241 367 606 - F +33 (0) 241 367 612 - i f R @ e R i c P r t

AMERICAS - E\_Ri\_C. - FR. La d e r d a l e - e R i c @ e R i c P r t

ASIA-PACIFIC - E\_Ri\_A i a P e L d - S i g a P r e - e R i a i a @ e R i c P r t

INDIA - E\_Ri\_I d i a - M. a i - e R i i d i a @ e R i c P r t

CHINA - E\_Ri\_C h i a - S h a g h a i - e R i c h i a @ e R i c P r t

www.evolis.com

